



**Weatherford®**

## ePRO™ Sensor Data Process System

Weatherford's production optimization group, eProduction Solutions (eP), offers the ePRO sensor data process system. The unit offers compact size with ease-of-use. The backlit LCD displays pressure and temperature data at a two sample-per-second rate.

Designed for ruggedness, the ePRO system can be pole mounted or building enclosed. Outdoors, from Northern Canada to Latin America, the unit can be installed with no special considerations for venting or heating.

A surface interface for the Weatherford's sPOD™ single-point digital sensor, the system's data storage and pressure signal output is ideal for use in your automation application.

A model solution for single well applications, the unit outputs a pressure control signal to variable speed drive controllers to automate your artificial lift equipment. With low power requirements for the entire system, pressure monitoring wells where line power does not exist is made simple.

Combine the system directly with the ePAC™ vector flux drive and your automation package is ready for use. With the addition of the Weatherford radio or SCADA interface, the ePRO system is ready to communicate from the most demanding environments.



### Specifications

#### General

Enclosure Dimensions	5" (12.7 cm) D x 7-3/8" (18.7 cm) W x 9-1/4" (23.5 cm) H, metal latch with lock clasp
Weight	5 lbs (2.27 kg)
Display	Dual line: pressure and temperature, backlit
Operating Temperature	-4° to +185°F (-20° to +85°C)
Configuration and Setup Interface	DB9-F, RS-232 PC serial communication
Host Software	Windows® 95, 98, NT, or 2000
Data Storage	3000 records
Storage Frequency	User defined, 30 seconds to 1 hour intervals
Communication Protocol	Modbus™ RTU
Field Termination Connections	Bi-level, fused screw terminal

#### Electrical

Voltage Input Requirement	24 Vdc
System Power Consumption	3.5 Watts (with sensor)
Back-up Battery	3.0 V lithium, static life (5.5 years)

#### Analog Outputs (AO)

Dedicated Pressure Output	4- to 20-mA, scaleable, requires 9- to 32-Vdc from remote side
Dedicated Temperature Output	4- to 20-mA, scaleable, requires 9- to 32-Vdc from remote side

#### Analog Inputs (AI)

None

#### Weatherford International Ltd.

515 Post Oak Blvd., Suite 600  
Houston, Texas 77027 USA  
Tel: 713-693-4000  
www.weatherford.com



Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at [www.weatherford.com](http://www.weatherford.com). For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.